

DYABLO – S504 S4 SRC



DESCRIPTION	NORMA EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: PVC/ nitrile rubber	5.4.2 Thickness	121 N	≥ 60 N
	5.4.5 Flexing resistance	1,4 mg/cm ² h	$\geq 0,8$ mg/cm ² h
SAFETY TOE CAP: Steel	5.3.2.3 Impact resistance	14,5 mm	≥ 14 mm
	5.3.2.4 Compression resistance	15 mm	≥ 14 mm
OUTSOLE: PVC/ nitrile rubber	5.8.3 Abrasion resistance	250 mm ³	≤ 250 mm ³
	5.8.4 Flexing resistance	2 mm	$\leq 4,0$ mm
	6.4.2 Oils resistance	-5,8%	$\leq 12\%$
	5.11 Pressed ceramic tile floor on detergent resistance	0,41	
	Flat slip	0,41	$\geq 0,32$
	Heel slip		$\geq 0,28$
	Stainless steel plate on glycerin resistance		
	Flat slip	0,19	$\geq 0,18$
	Heel slip	0,13	$\geq 0,13$

SIZES: 36-47

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207

www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it