

JUMBO DEFIANT®

FOR OVER PRESCRIPTION SPECTACLES



PART

ESB1010SJ**

LENS

☐ Clear

- Tilt type adjustment allows optimum visibility.
- Lenses are coated for superior scratch resistance.
- Lenses provide 99.9% protection against harmful UV rays.
- Temples adjust to four settings.
- For use over prescription spectacles.

GENERAL SPECIFICATION

Bridge: 34.4mm
Lens Base: 2.25 Curve
Lens Size Diagonal: 157.8mm
Lens Size Vertical: 66mm
Lens Thickness: 2.20mm
Overall Length [Lens-Tip]: 143-159mm
Overall Width [Hinge-Hinge]: 160mm
PD: 68mm
Weight: 45gm

PACKAGING

Polybag: 1 pc
Inner Box: 12 pcs
Case: 300 pcs

JUMBO DEFIANT®

FOR OVER PRESCRIPTION SPECTACLES

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Wrap around design with side protection
Frame	N/A	N/A
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Bridge-Polycarbonate	Integral to lens
Sleeve (on temple)	Nylon 6.6	Adjustable to 5 lengths
Temple	Nylon 6.6	Ratchet/tilt to multiple positions
Temple Tip	N/A	N/A
Hinge	Nylon 6.6	3 barrel type, integral to clip/sleeve
Screw	Brass	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB1010SJ	 Clear	2C - 1.2 P 1 S CE	CE P EN166 S

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust