

PROTOCOL®

SETS A STANDARD FOR OPTIMAL STYLE



PART

ESB6210D*

ESB6210DT*

ESB6220D*

ESB6220DT*

ESB6265D*

ESB6270D*

ESB6280D*

EST6215D*

LENS



Clear



Clear (Anti-Fog)



Gray



Gray (Anti-Fog)



Ice Blue Mirror



Silver Mirror



Indoor/Outdoor Mirror



Coffee

- Sets the standard for optimal style in safety eyewear, with clean lines and simple sophistication.
- Unisex design incorporates the elements of safety and fashion eyewear.
- Flexible PVC nose pads and temple tips generate a soft cushion for a high level of comfort.
- Scratch-resistant, polycarbonate lens provides 99.9% UV protection.

GENERAL SPECIFICATION

Bridge: 5mm

Lens Base: 8 Curve

Lens Size Diagonal: 76.5mm

Lens Size Vertical: 43mm

Lens Thickness: 2.2mm

Overall Length (Lens-Tip): 160mm

Overall Width (Hinge-Hinge): 134mm

PD: 68mm

Weight: 24gm

Closest point between lens: 12.5mm

Closest point between temples tip: 84mm

PACKAGING

Polybag: 1pc









Inner Box: 12 pcs

Case: 300 pcs

PROTOCOL®

SETS A STANDARD FOR OPTIMAL STYLE

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base wrap around lens
Frame	Polycarbonate	Lens clipped to frame
Nose Piece	PVC	Universal fit
Temple	Polycarbonate	Soft tips for comfort
Temple Tips	PVC	
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB6210D	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ESB6210DT	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB6220D	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESB6220DT	 Gray (Anti-Fog)	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB6265D	 Ice Blue Mirror	5 - 3.1 P 1 F CE	CE P EN166 F
ESB6270D	 Silver Mirror	5 - 2.5 P 1 F CE	CE P EN166 F
ESB6280D	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F CE	CE P EN166 F
EST6215D	 Coffee	5 - 2.5 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter

5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s

F: Low energy impact, resists a 6mm, 0.86g at 45 m/s

B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s

A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication

N: Filter with Anti-Fog features

CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard

P: Manufacture Indication

EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact

B: Medium energy impact

BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets

4: Protection against large dust