

# G204/G204T

## CHEMICAL GOGGLE



### PART

EG204\*\*

EG204T\*\*\*

### LENS

☐ Clear☐ Clear (Anti-Fog)

- Chemical splash goggle features vent caps to restrict influx of liquids.
- Lenses provide 99.9% protection against harmful UV rays.

### GENERAL SPECIFICATION

Bridge: N/A

Lens Base: Flat

Lens Size Diagonal: 144mm

Lens Size Vertical: 68mm

Lens Thickness: 2.0mm

Overall Length (Lens-Tip): N/A

Overall Width (Hinge-Hinge): 200mm

PD: 68mm

Weight: 79gm

### PACKAGING

Polybag: 1pc



Inner Box: 12 pcs

Case: 144 pcs

# G204/G204T

## CHEMICAL GOGGLE

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Lens inset in PVC frame
Frame	PVC	Polyvinyl Chloride
Nose Piece	PVC	Integral to frame
4 cap vents	LPDE	
Elastic Band	60% polyester 40% rubber thread	

PART	LENS	LENS MARKING	FRAME MARKING
EG204	 Clear	2 - 1.2 P 1 F CE	CE P EN166 F
EG204T	 Clear (Anti-Fog)	2 - 1.2 P 1 F CE	CE P EN166 F

### LENS MARKING

#### Code (field of use):

2 or 3: UV Filter  
5 or 6: Solar Filter

#### Color Perception:

C: Unimpaired color perception

#### Protection Class:

1.2 to 6: Degree of visible light filtration

#### Optical Class:

1: High optical quality / No optical distortion

#### Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s  
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s  
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s  
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

#### Symbols:

P: Manufacture Indication  
N: Filter with Anti-Fog features  
CE: European Standard

### FRAME MARKING

#### Symbols:

CE: European Standard  
P: Manufacture Indication  
EN166: CE specification for protective eyewear

#### Mechanical Strength:

F: Low energy impact  
B: Medium energy impact  
BT: Medium energy impact at extreme temperatures

#### Protection Class:

3: Protection against liquid droplets  
4: Protection against large dust