

FURIX™

WRAP-AROUND SUNGLASS STYLE



PART

SB8510DT***

SB8515DT***

SB8520DT***

SB8575DT***

LENS

 Clear (Anti-Fog)

 Coffee (Anti-Fog)

 Gray (Anti-Fog)

 Blue Mirror (Anti-Fog)

- Wrap-around, sunglass style fits all facial sizes.
- Provides 99.9% protection against harmful UV rays.
- First class optical lens provides unrestricted vision.
- Lightweight, contemporary frame is comfortable for both working environments and recreational activities.

GENERAL SPECIFICATION

Bridge: 13mm

Lens Base: 8 Curve

Lens Size Diagonal: 66mm

Lens Size Vertical: 38.8mm

Lens Thickness: 2.0mm

Overall Length (Lens-Tip): 145mm

Overall Width (Hinge-Hinge): 133+/-1mm

Weight: 35.6gm

Closest point between lens: 9mm





Closest point between temple tips: 95+/-5mm

FURIX™

WRAP-AROUND SUNGLASS STYLE

PACKAGING
Polybag: 1 pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base wrap around lens
Frame	Nylon	N/A
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8510DT	 Clear (Anti-Fog)	2C - 1.2 P 1 F CE	P EN166 CE
SB8515DT	 Coffee (Anti-Fog)	5 - 2.5 P 1 F CE	P EN166 CE
SB8520DT	 Gray (Anti-Fog)	5 - 2.5 P 1 F CE	P EN166 CE
SB8575DT	 Blue Mirror (Anti-Fog)	5 - 3.1 P 1 F CE	P EN166 CE

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust