

EXETER®

SPORTY STYLE WITH MAXIMUM PROTECTON



PART	LENS
ESB5110DT***	Clear (Anti-Fog)
ESB5120DT****	Gray (Anti-Fog)
ESB5155DT***	Sky Red Mirror Mirror (Anti-Fog)
ESB5170DT***	Silver Mirror (Anti-Fog)
ESB5175DT**	Blue Mirror (Anti-Fog)
EST5115DT***	Coffee (Anti-Fog)

- Sporty style with maximum protection.
- Curved lens with side window gives fashionable look with panoramic view.
- Durable frame gives a pressure free fit.
- Soft nose piece and rubber insert temple tips provide a comfortable fit.
- Scratch resistant lenses filter out 99.9% of harmful UV rays.

GENERAL SPECIFICATION
Bridge: 13.4mm
Closest Point Between Lens: 14.8mm
Closest Point Between Temple Tips: 93mm
Lens Base: 8 Curve
Lens Size Diagonal: 70.8mm
Lens Size Vertical: 44mm
Lens Thickness: 2.30mm
Overall Length (Lens-Tip): 157mm
Overall Width (Hinge-Hinge): 127.5mm
PD: 68mm
Weight: 29gm

EXETER®

SPORTY STYLE WITH MAXIMUM PROTECTION

PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Outer Carton: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, wrap around design with side protection
Side Window Lens	Polycarbonate	Along with the front lens makes full wrap around image
Frame	Nylon	Durable & flexible, sporty style
Nose Piece	PVC	Universal
Temple	Nylon	Spatula
Temple Tip	PVC	Comfortable & good for color variants
Hinge	Nylon	3 barrel type, integral to frame & temples
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB5110DT	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB5120DT	 Gray (Anti-Fog)	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB5155DT	 Sky Red Mirror Mirror (Anti-Fog)	5 - 3.1 P 1 F CE	CE P EN166 F
ESB5170DT	 Silver Mirror (Anti-Fog)	5 - 2.5 P 1 F CE	CE P EN166 F
ESB5175DT	 Blue Mirror (Anti-Fog)	5 - 2.5 P 1 F CE	CE P EN166 F
EST5115DT	 Coffee (Anti-Fog)	5 - 2.5 P 1 F N CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust