

PMXTREME® ANSI CE



Built-in rubber nosepiece

Ventilated flexible temples with rubber temple tips

Includes black lanyard cord

| Part No. | Black Frame with Cord | |
|---------------|-----------------------|-------|
| ESB6310STP ●● | AF | Clear |
| ESB6320STP ●● | AF | Gray |



PMXTREME® LED ANSI CE



Super bright swiveling LED bulbs (three lumens per side) allows you to see in dark places while keeping your hands free

Built-in rubber nosepiece and rubber temples tips

The alkaline batteries provide up to 50 hours of use before replacing. Three L44 alkaline batteries per temples (six total) are included

Easy to use push button on/off switches are located at the top of each temple

| Part No. | Black Frame | |
|------------------|-------------|-------|
| ESB6310STPLED ●● | AF | Clear |



PMXTREME®

General Specifications

Weight: 27 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

| Part No. | Lens Marking | Temple Marking |
|------------|----------------------|----------------|
| ESB6310STP | 2 - 1.2 P 1 F K N CE | CE P EN166 F |
| ESB6320STP | 5 - 3.1 P 1 F K N CE | CE P EN166 F |

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark

EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

PMXTREME LED

General Specifications

Weight: 50 gm
 PD: 72 mm
 Bridge: 14 mm
 Lens base: 9 curve
 Lens size diagonal: 78 mm
 Lens size vertical: 46 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 103 mm
 Overall width (hinge - hinge): 140 mm

Materials

Lens: polycarbonate
 Temple: nylon
 Frame: nylon
 Screw: stainless steel
 Nosepiece: rubber
 Temple tips: rubber

| Part No. | Lens Marking | Temple Marking |
|---------------|----------------------|----------------|
| ESB6310STPLED | 2 - 1.2 P 1 F K N CE | CE P EN166 F |

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark

EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

