



**Cappture™** ANSI CE CSA



Dielectric  
 Designed to better fit today's prescription eyewear  
 Temples extend from browbar to avoid interference with prescription frame's temples  
 Rubber gasket is available in select options



Part No.	Lens and Temples	
ES9910ST ●●●	AF	Clear H2X
ES9920ST ●●●	AF	Gray H2X
Part No.	Rubber Gasket	
ES9910STMRG ●●●	AF	Clear H2MAX
ES9920STMRG ●●●	AF	Gray H2MAX



[vimeo.com/pyramex/h2max](https://vimeo.com/pyramex/h2max)

There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) and Canadian (CSA Z94.3) (●) standards. For specific lens options visit our website or contact your sales representative.

## Cappture™

### General Specifications

Weight: 29.5 gm | 51.7 gm with rubber gasket  
 Bridge: 23.1 mm  
 Lens base: 2.5 curve  
 Lens size diagonal: 145.7 mm  
 Lens size vertical: 51.5 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 160 mm  
 Overall width (hinge - hinge): 132.5mm  
 Closest point between temple tips: 88 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate  
 Hinge: polycarbonate  
 Nosepiece: polycarbonate  
 Rubber gasket: polycarbonate and thermoplastic rubber (TPR)

### Part No.

### Lens Markings

### Frame Markings

ES9910ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ES9920ST	5 -2.5 P 1 F N CE	CE P EN166 F
ES9910STMRG	2 C - 1.2 P 1 F K N CE	CE P EN166 F
ES9920STMRG	5 -2.5 P 1 F K N CE	CE P EN166 F

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Color perception

C: Unimpaired color perception

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 K: Resistance to surface damage by fine particles  
 N: Filter with anti-fog  
 CE: Europe standard

### Frame Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com