

TECHNICAL SHEET



Article:	B1205 I-BIT
Norm:	UNI EN ISO 20345:2011
Safety Class:	S1P ESD SRC
ESD protection of electronic components:	CEI EN 61340-5-1:2016, CEI EN 61340-4-5:2018 and CEI EN 61340-4-3:2018
Footwear height:	Mod. A, H 84 mm (< 113 mm, Rif. EN 20345-5.2.2)
Width:	11,5
Construction:	STROBEL; CEMENTED BIDENSITY SOLE PU/TPU ESD
Cleaning and maintenance:	Use only soft brushes and water. Do not use substances such as alcohol, thinners, gasoline, oil or any other chemicals. Keep the footwear, dry and clean, in a proper place at room temperature.
Suggested fields:	Electronics (EPA=Electrostatic protected areas ESD), automotive, automated lines, building

ESD Protection (Electrostatic discharges) for electronic devices

Suitable for use in EPA areas (Electrostatic discharges protected area)

Component	Description	Value	Norm Requirements
Entire footwear	Total resistance footwear/ground (footwear worn on a metal ground)	3,17 x 10 ⁷ Ω	< 1,00 x 10 ⁸ Ω
	Sole electrical transversal resistance (footwear resistance)	6,1 x 10 ⁷ Ω	≤ 1,00 x 10 ⁸ Ω
	Chargeability	20,9 V	< 100 V

Entire footwear: protections

Component	Description	Value	Norm Requirements	EN 20345
Composite SLIM CAP toe-cap	Impact resistance (200 J)			
	• Free height after impact	15,0 mm	≥ 14 mm	5.3.2.3
Sole (SRC)	Compression resistance (15 kN)			
	• Free height after compression	18,0 mm	≥ 14 mm	5.3.2.4
Fresh'n Flex (P)	Slip resistance			
	• SRA – Sole (entire sole)	0,46	≥ 0,32	5.3.5.4
	• SRA – Heel (Angle of 7°)	0,44	≥ 0,28	5.3.5.4
	• SRB – Sole (entire sole)	0,18	≥ 0,18	5.3.5.4
• SRB – Heel (Angle of 7°)	0,13	≥ 0,13	5.3.5.4	
Footbed (A)	Puncture resistance	No perforation	≥ 1100 N	6.2.1.1.2
Sole/Upper Heat (HI) Cold (CI)	Antistatic properties			
	• Electrical resistance	dry 5,6 x 10 ⁷ Ω humid 2,5 x 10 ⁷ Ω	≥ 10 ⁵ Ω , ≤ 10 ⁹ Ω ≥ 10 ⁵ Ω , ≤ 10 ⁹ Ω	6.2.2.2 6.2.2.2
Heel (E)	Thermal insulation			
	Insole temperature increase	N/A	≤ 22°C	6.2.3.1
(WR) (M)	Insole temperature decrease	N/A	≤ 10°C	6.2.3.2
	Shock-absorption in the heel region	30 J	≥ 20 J	6.2.4
	Water resistance (Water absorption)	N/A	≤ 3 cm ²	6.2.5
	Metatarsal protection	N/A	≥ 40 mm	6.2.6

Upper

Component	Description	Value	Norm Requirements	EN 20345
Velour microfiber	Tear resistance	71 N	≥ 60 N	5.4.3
	Traction resistance	N/A	≥ 15 N/mm ²	5.4.4
Water steam permeability	Water steam permeability	3,5 mg/cm ² h	≥ 0.8 mg/cm ² h	5.4.6
	Water steam coefficient	30 mg/cm ²	≥ 15 mg/cm ²	5.4.6
	pH value	N/A	≥ 3,2	5.4.7
	Chromium VI	N/A	Not detectable	5.4.9
	Water passed	N/A	≤ 0.2 g	6.3
	Water absorption	N/A	≤ 30%	6.3

Lining				
Component	Description	Value	Norm Requirements	EN 20345
3D Fabric	Tear resistance	47 N	≥ 15 N	5.5.1
	Abrasion resistance	<ul style="list-style-type: none"> Dry : the surface shows no holes humid: the surface shows no holes 	No holes till 51.200 cycles	5.5.2
	Water steam release	21,1 mg/cm ² h	≥ 2,0 mg/cm ² h	5.5.3
	pH value	N/A	Not detectable	5.5.4
	Chromium VI	N/A	Not detectable	5.5.5

Insole				
Component	Description	Value	Norm Requirements	EN 20345
Fresh'n Flex ESD	Thickness	3,7 mm	≥ 2,0 mm	5.7.1
	pH value	N/A	Not detectable	5.7.2
	Water absorption	102 mg/cm ²	≥ 70 mg/cm ²	5.7.3
	Water release	97%	≥ 80 %	5.7.3
	Abrasion resistance (after 400 cycles)	No damage	Damage ≤ to norms reference	5.7.4.1
	Chromium VI	N/A	Not detectable	5.7.5

Removable footbed*				
Component	Description	Value	Norm Requirements	EN 20345
DRY'N AIR OMNIA ESD WEARECO	Thickness	3,5 ± 0,5 mm	N/A	5.5.1
	Ph value	N/A	Not detectable	5.5.2
	Water absorption	Permeable through the holes	Permeable or ≥ 70mg/cm ²	5.5.3
	Water release	Permeable through the holes	Permeable or ≥ 80%	5.5.3
	Abrasion resistance	No damage	Dry No holes till 25.600 cycles Humid no holes till 12.800 cycles	5.5.4.2
	Chromium VI	N/A	Not detectable	5.7

* Compatible with DRY'N AIR SCAN&FIT OMNIA and Dry'n AIR OMNIA ESD insoles

Sole				
Component	Description	Value	Norm Requirements	EN 20345
PU Midsole	Sole thickness without profiles	6,5 mm	≥ 4 mm	5.8.1.1
	Profiles height	4,5 mm	≥ 2,5 mm	5.8.1.3
	Tear resistance	8,7 kN/m	≥ 8 kN/m	5.8.2
TPU ESD Outsole	Abrasion resistance <ul style="list-style-type: none"> relative volume loss 	73 mm ³	≤ 250 mm ³	5.8.3
	Flexion resistance <ul style="list-style-type: none"> Notches increase after 30.000 cycles 	2 mm	≤ 4 mm	5.8.4
TPU ESD Outsole	Hydrolysis <ul style="list-style-type: none"> Notches increase after 150.00 cycles 	2,5 mm	≤ 6 mm	5.8.5
	Outsole – insole detachment	4,5	≥ 4 N/mm; (*) _≥ 3 N/mm with sole ripping	5.8.6
	(HRO) Contact heat resistance (300°C)	No damage	No damage (melting, breaking)	6.4.1
	(FO) Fuel resistance (volume changes)	9 %	≤ 12%	6.4.2

Date: 02/07/2021

Copy in accordance with the Italian sheet