

# Dräger X-plore 1700 Filterierende Halbmasken



## MASKE ANLEGEN



1  
Vor dem Aufsetzen positionieren Sie die Maske geöffnet in Ihrer Handfläche. Dabei sollten die Bänder unter der Hand verlaufen.



2  
Führen Sie nun die Atemschutzmaske an Ihr Gesicht und ziehen Sie das erste Band über den Kopf in den Nacken.



3  
Platzieren Sie nun das zweite Band in Höhe des Hinterkopfes über den Ohren.



4  
Für einen hohen Dichtsitz, ist es erforderlich den Nasenbügel so anzupassen, dass die Maske im oberen Nasenbereich keine Leckagen aufweist.

## DICHTPRÜFUNG: VOR JEDEM EINSATZ!



5  
Prüfen Sie die Dichtigkeit indem Sie die Halbmaske mit beiden Händen bedecken und kräftig ausatmen. Dabei sollte sich in der Maske ein leichter Druck aufbauen. Sollte Luft an den Rändern entweichen, korrigieren Sie bitte den Maskensitz und die Anpassung.



Einsatzbereit.

**Warnung:** Bärte können den erforderlichen dichten Sitz der Halbmaske beeinträchtigen und Leckagen verursachen – Vergiftungsgefahr! Einsatz nur mit dichter Halbmaske antreten.

Dieses Poster ersetzt nicht das Lesen und Verstehen der Gebrauchsanweisung der eingesetzten Maske. Die Gebrauchsanweisung muss vor dem Gebrauch der Maske genau gelesen und verstanden werden!

Nichtbeachtung der Gebrauchsanweisung kann zu Krankheit oder Tod führen!

Bei Rückfragen bitte Ihren Sicherheitsbeauftragten oder Ihre zuständige Dräger-Organisation unter Rufnummer +49 451 882-0 ansprechen.

# Dräger X-plore 1700 Filtering Face Pieces



## DONNING THE MASK



1

Hold the mask in your hand with the head straps hanging down.



2

Position the mask under your chin and over your nose. Slip the first strap over your head to the back of your neck.



3

Pull the upper strap into position at the back of your head, ensure the strap sits above your ears.



4

Adjust the nose clip to minimize leakage.

## USER SEAL CHECK



5

Cover the mask with both hands and exhale. The mask should inflate slightly. If any air escapes at the sides of the mask, readjust the mask until it fits properly and ensure that the nose clip is positioned correctly on your nose.



Ready for use.

**Warning:** Beards in the sealing area of the mask can cause leaks. Always make sure the mask forms a tight seal prior to entering a hazardous atmosphere.

This poster is not a replacement for reading and understanding the instructions for use prior to using the specified mask! Failure to do so could result in sickness or death! For further assistance concerning proper use, ask your supervisor or call your local Dräger organization at +49 451 882-0.

# Dräger X-plore 1700 Particulate Respirators



## DONNING THE MASK



1

Hold the mask in your hand with the head straps hanging down.



2

Position the mask under your chin and over your nose. Slip the first strap over your head to the back of your neck.



3

Pull the upper strap into position at the back of your head, ensure the strap sits above your ears.



4

Adjust the nose clip to minimize leakage.

## USER SEAL CHECK



5

Cover the mask with both hands and exhale. The mask should inflate slightly. If any air escapes at the sides of the mask, readjust the mask until it fits properly and ensure that the nose clip is positioned correctly on your nose.



Ready for use.

**Warning:** Beards in the sealing area of the mask can cause leaks. Always make sure the mask forms a tight seal prior to entering a hazardous atmosphere.

This poster is not a replacement for reading and understanding the instructions for use prior to using the specified mask! Failure to do so could result in sickness or death! For further assistance concerning proper use, ask your supervisor or call your local Dräger organization at +1 800 922 5518.