



PYRAMEX

Perform At Your Peak

Ever-Lite® ANSI CE CSA



RUBBER NOSEPIECE



CO-INJECTED TEMPLES

Soft nosepiece for snug fit

Slim co-injected temples

Lightweight spectacle – 22 gm

Part No.	Black Frame
ESB8610D ●●●	Clear
ESB8610DT ●●●	AF Clear H2X
ESB8610DTM ●●●	AF Clear H2MAX
ESB8620D ●●●	Gray
ESB8620DT ●●●	AF Gray H2X
ESB8620DTM ●●●	AF Gray H2MAX
ESB8624D ●●●	Photochromic
ESB8630D ●●●	Amber
ESB8680D ●●●	I/O Mirror
ESB8680DT ●●●	AF I/O Mirror



vimeo.com/pyramex/h2max



Note: Photochromic lens changes from clear to dark, after exposed to direct UV light. Changes from dark to clear, after removed from UV light.

There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

Meets European [EN166] (●) and ANSI Z87.1+ (●) standards. All lenses are hard coated polycarbonate scratch-resistant and provide 99% protection from harmful UV rays. Some options meet and Canadian [CSA Z94.3] (●) standards.

Ever-Lite®

General Specifications

Weight: 22 gm
 PD: 64 mm
 Bridge: 11.2 mm
 Lens base: 8 curve
 Lens size diagonal: 79.6 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 134.3 mm
 Closest point between temple tips: 70 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
ESB8610D	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB8610DT	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB8610DTM	2C-1.2 P 1 F K N CE	CE P EN166 F
ESB8620D	5 -2.5 P 1 F CE	CE P EN166 F
ESB8620DT	5 -2.5 P 1 F N CE	CE P EN166 F
ESB8620DTM	5-2.5 P 1 F K N CE	CE P EN166 F
ESB8624D	5-1.4<2 P 1 F CE	CE P EN166 F
ESB8630D	2 - 1.2 P 1 F CE	CE P EN166 F
ESB8680D	5 -1.7 P 1 F CE	CE P EN166 F
ESB8680DT	5 -1.7 P 1 F N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

