

VENTURE II® READERS

STRATEGICALLY PLACED LENS INSERTS



| PART | LENS |
|--------------|-------------------------------------|
| ESB1810R10** | <input type="checkbox"/> Clear +1.0 |
| ESB1810R15** | <input type="checkbox"/> Clear +1.5 |
| ESB1810R20** | <input type="checkbox"/> Clear +2.0 |
| ESB1810R25** | <input type="checkbox"/> Clear +2.5 |
| ESB1810R30** | <input type="checkbox"/> Clear +3.0 |

- Temples adjust to four different lengths.
- 9.75 base curved lens provides full side protection.
- Strategic placement of lens insert is out of user's direct line of vision.
- Nose buds secure the glass and prevent slipping while providing a pillow soft fit.

| GENERAL SPECIFICATION |
|--|
| Bridge: 10.5mm |
| Lens Base: 9.75 Curve |
| Lens Size Diagonal: 56mm |
| Lens Size Vertical: 45mm |
| Lens Thickness: 2.2mm |
| Overall Length (Lens-Tip): 150-163mm |
| Overall Width (Hinge-Hinge): 142mm |
| PD: 68mm |
| Weight: 27gm |
| Closest point between lens: 7mm |
| Closest point between temple tips: 95-98mm |

VENTURE II® READERS

STRATEGICALLY PLACED LENS INSERTS






PACKAGING

Polybag: 1pc

Inner Box: 6 pcs

Outer Carton: 150 pcs

| COMPONENT | MATERIAL | FEATURES |
|-------------|------------------------|--------------------------|
| Lens | Polycarbonate | Full eye protection |
| Frame | Polycarbonate | Lens clip in frame |
| Side Shield | Polycarbonate | Integral to lens |
| Nose Piece | Bridge - Polycarbonate | Integral to lens |
| | Nose Pad - PVC | Snap in nose piece |
| Sleeve | Nylon | 4 length position adjust |
| Temple | Nylon | Length adjustable |
| Hinge | Polycarbonate/Nylon | 3 barrel type |
| Screw | Stainless steel | Standard hinge screw |

| PART | LENS | LENS MARKING | FRAME MARKING |
|------------|--|-------------------|---------------|
| ESB1810R10 |  Clear +1.0 | 2C - 1.2 P 1 F CE | CE P EN166 F |
| ESB1810R15 |  Clear +1.5 | 2C - 1.2 P 1 F CE | CE P EN166 F |
| ESB1810R20 |  Clear +2.0 | 2C - 1.2 P 1 F CE | CE P EN166 F |
| ESB1810R25 |  Clear +2.5 | 2C - 1.2 P 1 F CE | CE P EN166 F |
| ESB1810R30 |  Clear +3.0 | 2C - 1.2 P 1 F CE | CE P EN166 F |

LENS MARKING

Code (field of use):

2 or 3: UV Filter

5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s

F: Low energy impact, resists a 6mm, 0.86g at 45 m/s

B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s

A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication

N: Filter with Anti-Fog features

CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard

P: Manufacture Indication

EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact

B: Medium energy impact

BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets

4: Protection against large dust