

GG504T

CAPSTONE® 500 SERIES



PART
EGG504T*****

LENS
 Clear (Anti-Fog)

- Fits over prescription glasses.
- Cylinder lens is coated to prevent fogging.
- Soft PVC body conforms to facial contours for comfort fit.
- Dual purpose goggle adaptable to many different applications.
- Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance.

GENERAL SPECIFICATION
Bridge: 45mm
Lens Base: 5.5 curve
Lens Size Diagonal: 154mm
Lens Size Vertical: 78mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 91mm
Overall Width (Hinge-Hinge): 180mm
PD: 68mm
Weight: 92gm
Strap Length: 540mm
Closest point between temple tips: N/A, strap
Closest point between temple tips: N/A, single lens
Case Weight: 49.76lbs
Case Pack: 144

PACKAGING
Polybag: 1pc
Bulk in an outer carton: 144 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Single & cylinder lens
Body	PVC	Polyvinyl chloride, flexible fit
	Polycarbonate	Vent parts for air flow
Nose Piece	PVC	Universal integral to frame
Headband	Textile Elastic	Adjustable Elastic

PART	LENS	LENS MARKING	FRAME MARKING
EGG504T	Clear (Anti-Fog)	2C - 1.2 P 1 BT N CE	CE P EN166 3 4 BT

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
 F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
 B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
 A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
 N: Filter with Anti-Fog features
 CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
 P: Manufacture Indication
 EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
 B: Medium energy impact
 BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
 4: Protection against large dust