

CORTEZ®

EXTREMELY STYLISH AND COMFORTABLE



PART	LENS
ESB3610S**	<input type="checkbox"/> Clear
ESB3610ST***	<input type="checkbox"/> Clear (Anti-Fog)
ESB3620S**	<input checked="" type="checkbox"/> Gray
ESB3680S**	<input type="checkbox"/> Indoor/Outdoor Mirror

- Single lens design provides maximum protection.
- Durable dual injected polycarbonate and rubber temples.
- Riddled, cushioned nosepiece fits a wide range of bridge sizes and protects against slippage.
- Scratch-resistant, hard-coated polycarbonate lens filter out more than 99.9% of harmful UV rays.





GENERAL SPECIFICATION
Bridge: 12mm
Closest Point Between Lens: 15.5mm
Closest Point Between Temple Tips: 73mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 70mm
Lens Size Vertical: 43mm
Lens Thickness: 2.20mm
Overall Length (Lens-Tip): 157mm
Overall Width (Hinge-Hinge): 137mm
PD: 68mm
Weight: 23gm

CORTEZ®

EXTREMELY STYLISH AND COMFORTABLE

PACKAGING
Polybag: 1 pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9.5 curve lens, wrap around design with side protection
Frame	N/A	N/A
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Bridge-Polycarbonate	Integral to lens
	Nose piece- PVC	Snap & glue in nose piece
Sleeve (on temple)	N/A	N/A
Temple	Side Arm Polycarbonate	Spatula, two material co-injection
		Durable PC temple with soft cushion tip
Temple Tip	TPE	Soft to prevent slippage
Hinge	Polycarbonate	5 barrel type, integral to frame/temple
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB3610S	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ESB3610ST	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB3620S	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESB3680S	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust