

MAYAN®

DUAL FOCUS LENS AND RATCHETING TEMPLES



PART	LENS
ESB2610D*	<input type="checkbox"/> Clear
ESB2610DP*	<input type="checkbox"/> Clear
ESB2620D*	<input checked="" type="checkbox"/> Gray

- Lenses block 99.9% of harmful UV rays.
- Crafted of high grade nylon and polycarbonate materials.
- Sleek in-line ratchet adjustable temples provides perfect fit.
- Fashionable, soft rubber straight back temples- no length adjustment necessary.




GENERAL SPECIFICATION
Bridge: 15.5mm
Closest Point Between Temple Tips: 86mm
Lens Base: 9 Curve
Lens Size Diagonal: 83.5mm
Lens Size Vertical: 48.5mm
Lens Thickness: 2.4mm
Overall Length [Lens-Tip]: 160mm
Overall Width [Hinge-Hinge]: 139mm
PD: 68mm
Weight: 28gm

MAYAN®

DUAL FOCUS LENS AND RATCHETING TEMPLES

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Height curvature dual focus construction, fit the contours of the face
Frame	Polycarbonate	Streamline, lightweight, fashionable
Side Shields	Polycarbonate	Integral to lens
Nose Bridge	Polycarbonate	V-Bridge, integral to lens
Sleeve Temple	Polycarbonate	Unique ratchet mechanism with style slim design, unique ratchet mechanism allows users to adjust lens angle for a custom fit
Soft Temple Tip	PVC	Brand new soft temple tips give ultimate comfort fit and prevent slippage
Hinge	Polycarbonate	3 barrel type, integral to frame/part (temple)
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB2610D	 Clear	2C - 1.2 P 1F CE	CE P EN166 F
ESB2610DP	 Clear	2C - 1.2 P 1F CE	CE P EN166 F
ESB2620D	 Gray	5 - 2.5 P 1F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust