

RENDEZVOUS®

FULLY ADJUSTABLE SPECTACLES



PART	LENS	PART	LENS
ESB2810S**	Clear	ESB2840S**	Orange
ESB2810ST***	Clear (Anti-Fog)	ESB2870S**	Silver Mirror
ESB2815S**	Coffee	ESB2875S**	Blue Mirror
ESB2820S**	Gray	ESB2880S**	Indoor/Outdoor Mirror
ESB2830S**	Amber		

- Temples adjust to four different lengths.
- Adjustable nose pad conforms to broad range of bridge sizes.
- Crafted from high grade polycarbonate, machined from virgin materials and formed to shape.
- Align lens angle to proper position for work application with ratcheting lens pitch adjustment.
- 9.5 base curve lens provides excellent side protection against wind and airborne particles, provides 99.9% protection against harmful UV rays.










GENERAL SPECIFICATION
Bridge: 9.6mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 83mm
Lens Size Vertical: 45.5mm
Lens Thickness: 2.42mm
Overall Length (Lens-Tip): 54-166mm
Overall Width (Hinge-Hinge): 138mm
PD: 68mm
Weight: 28gm
Closest point between lens: 16.6mm
Closest point between temples tip: 75-76mm

RENDEZVOUS®

FULLY ADJUSTABLE SPECTACLES

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Contemporary design with dual-focus construction to fit contours of face
Frame	Polycarbonate	Lightweight & durable ventilation reduces chance of fogging
Side Shield	Polycarbonate	Integral to lens, provides excellent coverage
Nose Bridge	Polycarbonate	Break-through design, fully adjustable, soft touch & support, no pressure and slippage
Soft Nose Pad	PVC	
Sleeve (on temple)	Polycarbonate	Unique ratchet mechanism with length adjustable temple to create a custom fit. Slim design makes entire glass stylish & attractive
Temple		
Hinge	Polycarbonate	3 barrel type, integral to frame/ part (sleeve)
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB2810S	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ESB2810ST	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB2815S	 Coffee	5 - 2.5 P 1 F CE	CE P EN166 F
ESB2820S	 Gray	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB2830S	 Amber	2 - 1.2 P 1 F CE	CE P EN166 F
ESB2840S	 Orange	2 - 1.7 P 1 F CE	CE P EN166 F
ESB2870S	 Silver Mirror	5 - 2.5 P 1 F CE	CE P EN166 F
ESB2875S	 Blue Mirror	5 - 2.5 P 1 F CE	CE P EN166 F
ESB2880S	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust