







PMXSLIM®

SLIM FIT FOR SMALLER FACIAL FEATURES



PART	LENS
ESB7110S**	 Clear
ESB7110ST***	 Clear (Anti-Fog)
ESB7120S**	 Gray
ESB7120ST***	 Gray (Anti-Fog)
ESB7138S***	 Sandstone Bronze
ESB7180S***	 Indoor/Outdoor Mirror

- PMXSLIM has a slim fit for smaller facial features.
- Lenses provide 99.9% protection against harmful UV rays.
- Dual injected temple design includes soft rubber tips for a non-slip fit.
- Soft, adjustable PVC nose piece generates a cushion for all day comfort.
- High quality optics provide a clear, panoramic view without obstruction.
- Wrap-around, single lens design performs with incredible 10 base curve, including side protection that extends to the temples.







GENERAL SPECIFICATION
Bridge: 14.5mm
Closest Point Between Lens: 9mm
Closest Point Between Temple Tips: 86mm
Lens Base: 10 Curve
Lens Size Diagonal: 137.7mm
Lens Size Vertical: 45mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 170mm
Overall Width (Hinge-Hinge): 129mm
PD: 68mm
Weight: 25g

PMXSLIM®

SLIM FIT FOR SMALLER FACIAL FEATURES

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Hinge	Polycarbonate	3 barrel type, integral to lens/temples
Lens	Polycarbonate	10 base curve, wrap around design with side protection extended to temples
Temple Tips	Polycarbonate	Spatula with soft tip end
	TPE	
Side Shields	Polycarbonate	Integral to Lens
Nose Piece	PVC	Slip on type, pillow softness
Screw	Stainless Steel	Standard hinge screw
Frame	Polycarbonate	Integral to Lens

PART	LENS	LENS MARKING	FRAME MARKING
ESB7110S	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ESB7110ST	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ESB7120S	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESB7120ST	 Gray (Anti-Fog)	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB7138S	 Sandstone Bronze	5 - 2.5 P 1 F CE	CE P EN166 F
ESB7180S	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F N CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust