



PYRAMEX
Perform At Your Peak



Sitecore™ ANSI CE CSA



RUBBER
NOSEPIECE



RATCHETING
TEMPLES



ADJUSTABLE
TEMPLES

Built-in rubber nosepiece

Flexible and ventilated temples

Ratcheting temples

Temples adjust to three different lengths

Part No.	Gray and Lime Frame
ESGL10110D ●●●	Clear
ESGL10110DTM ●●●	AF Clear H2MAX
ESGL10120D ●●●	Gray
ESGL10120DTM ●●●	AF Gray H2MAX
ESGL10180D ●●●	I/O Mirror



vimeo.com/pyramex/h2max

There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●), Canadian CSA Z94.3 (●) – SEI third-party certification.

Sitecore™

General Specifications

Weight: 24.4 gm
 Bridge: 10.6 mm
 Lens base: 8 curve
 Lens size diagonal: 74 mm
 Lens size vertical: 41.5 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 158 mm
 Overall width (hinge - hinge): 132.5 mm
 Closest point between temple tips: 55 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Nosepiece: thermoplastic rubber (TPR)
 Ratchet: polycarbonate
 Sleeve: nylon
 Temple: nylon
 Screw: stainless steel

Part No.	Lens Marking	Temple Marking
ESGL10110D	2 C - 1.2 P 1 F CE	CE P EN166 F
ESGL10110DTM	2 C - 1.2 P 1 F K N CE	CE P EN166 F
ESGL10120D	5 -2.5 P 1 F CE	CE P EN166 F
ESGL10120DTM	5 -2.5 P 1 F K N CE	CE P EN166 F
ESGL10180D	5 -1.7 P 1 F CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Colour perception

C: Unimpaired colour perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

