



PYRAMEX

Perform At Your Peak



Torser™ ANSI CE CSA



DIELECTRIC

Dielectric

Flexible rubber gasket

Ratchet elastic headband with quick-fit retainer

Passes D3: Droplet and Splash Test – provides protection from droplets and splashes

Passes D4: Dust Test – provides protection from dust particles



vimeo.com/pyramex/h2max



Part No. **Black Body**

EGB10010TM ●●●

AF Clear **H2MAX**

Part No. **Black Body**

EGB10020TM ●●●

AF Grey **H2MAX**

There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European EN166 (●), Canadian CSA Z94.3 (●) – SEI third-party certification.

Torser™

General Specifications

Weight: 46.8 gm
 Bridge: 15 mm
 Lens base: 8 curve
 Lens size diagonal: 70.6 mm
 Lens size vertical: 49.8 mm
 Lens thickness: 2.0 mm
 Strap length: 580 mm
 Overall width (hinge - hinge): 70 mm
 Closest point between lens: 15 mm
 Closest point between strap holders: 145 mm

Materials

Lens: polycarbonate
 Strap holder: nylon
 Headband: polyester
 Quick-release button: nylon
 Nosepiece: thermoplastic elastomers (TPE)
 Body: polycarbonate & thermoplastic elastomers (TPE)

Part No.	Lens Marking	Temple Marking
EGB10010TM	2 C - 1.2 P 1 F K N CE	CE P EN166 F 3 4
EGB10020TM	5 -2.5 P 1 F K N CE	CE P EN166 F 3 4

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Colour perception

C: Unimpaired colour perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear
 3: D3 Droplet and Splash Test

4: D4: Dust Test

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

[P] +44 (0) 1635 254220 | [E] info@pyramexeurope.com